



Straight & angle cut HSS cut-off machine

Ref: PF 315

STANDARD EQUIPMENT

- Cutter: Ø 315 mm (not included)
- Motor 3HP, three-phase 400 V, 1500 rpm
- Pendulum descent controlled by a gear lever
- Graduated head & table, swivelling 45° to the left and to the right
- Variable rotation speed by potentiometer (N rpm = 19 to 64)
- Reduction by wheel and worm
- Tightening on each side of the blade
- Length & depth stops
- Welded structure with electro-pump, collection tank and chip drawer
- Double casing and electrical safety devices.
- CE certified machine



CUTTING CAPACITIES

Unit (mm)

90° cut	70	900	140x80
45° cut	60	80	100x70

OPTIONAL EQUIPMENT

- **SET OF 4 SPECIAL CLAMPS V-SHAPE:** *plastic or cast iron material*
- **PENUMATIC CLAMP**

ACCESSOIRES

- **HORIZONTAL ROLLER CONVEYOR** (*model: metal sheet between rollers*) :
 - Length: 3000 x 200 mm
 - Rollers Ø 40, roller spacing: 333mm, permissible load: 60 kg/m
- **LENGTH STOP SYSTEM FOR HORIZONTAL ROLLER CONVEYOR :**
 - Includes a graduated slide and a stop slide with locking device and manual removal
 - **GUIDAL WITH GRADUED RULER in mm** : length 1 000 mm or more
 - **GUIDAL LCD WITH LCD SCREEN from 0,1 mm** : length 1 000 mm or more

ROTY & FILS SAS – 41 rue Jacques Cartier – 35430 La Ville es Nonais – France

Tel : +33 (0)2 99 58 40 47

E-mail : contact@roty-tyro.com

www.roty-tyro.com