



# Swivel abrasive cutting machine – straight or angle cutting

Ref: TP 350



## STANDARD EQUIPMENT

- Grinder : Ø 350 mm, bore : 25,4 mm
- Motor 7.5 HP, three phase 400 V
- Swivel head & table: 45° to the left & 135° to the right
- Oscillating head movement: 150 mm (front to back)
- Manual clamping: 1 vice (pneumatic in option)
- Working height: 840 mm
- Length & depth stops
- Welded structure
- Double safety protection: safety cover + electric securities
- Table size: 550 x 340 x 60mm
- CE certified machine



CUTTING CAPACITIES			
90° cut	90	110	240x80
45° cut	80	110	180x60
30° cut	70	90	120x50

## OPTIONAL EQUIPMENT

- **LIGHT 24V**
- **PNEUMATIC VICE**
- **BI-MANUAL COMMAND**
- **CUT-OFF WHEELS:** Bore 25.4 mm – disk: Ø 350 mm

## ACCESSORIES

- **HORIZONTAL ROLLER CONVEYOR** (model: metal sheet between rollers) :
  - Length: 3000 x 200 mm
  - Rollers Ø 40 mm - roller spacing: 333 mm, permissible load: 60 kg/m
- **LENGTH STOP SYSTEM FOR HORIZONTAL ROLLER CONVEYOR :**
  - Includes a graduated slide and a stop slide with locking device and manual removal
  - **GUIDAL WITH GRADUED RULER in mm :** length 1000 mm or more
  - **GUIDAL LCD WITH LCD SCREEN from 0,1 mm :** length 1000 mm or more

ROTY & Fils – 64 rue de la Ville-Es-Cours – Z.I. Sud – 35400 SAINT-MALO – FRANCE

Tel : +33 (0)2 99 58 40 47

E-mail : [contact@roty-tyro.com](mailto:contact@roty-tyro.com)

[www.roty-tyro.com](http://www.roty-tyro.com)



# Swivel abrasive cutting machine – straight or angle cutting

Ref: TP 400



## STANDARD EQUIPMENT

- Grinder: Ø 406 mm, bore: 25,4 mm
- Motor 10 HP, three phase 400 V
- Swivel head & table: 45° to the left & 135° to the right
- Oscillating head movement: 150 mm (front to back)
- Manual clamping: 1 vice (pneumatic in option)
- Working height: 840 mm
- Length & depth stops
- Welded structure
- Double safety protection: safety cover + electric securities
- Table size: 550 x 340 x 60 mm
- CE certified machine

CUTTING CAPACITIES			
			
90° cut	110	130	240x90
45° cut	90	120	180x70
30° cut	80	100	120x70



## OPTIONAL EQUIPMENT

- **LIGHT 24V**
- **PNEUMATIC VICE**
- **BI-MANUAL COMMAND**
- **CUT-OFF WHEELS:** Bore 25.4 mm - disk: Ø 406 mm

## ACCESSORIES

- **HORIZONTAL ROLLER CONVEYOR** (model: metal sheet between rollers) :
  - Length: 3000 x 200 mm
  - Rollers Ø 40 mm - roller spacing: 333 mm, permissible load: 60 kg/m
- **LENGTH STOP SYSTEM FOR HORIZONTAL ROLLER CONVEYOR :**
  - Includes a graduated slide and a stop slide with locking device and manual removal
  - **GUIDAL WITH GRADUED RULER in mm :** length 1000 mm or more
  - **GUIDAL LCD WITH LCD SCREEN from 0,1 mm :** length 1000 mm or more

ROTY & Fils – 64 rue de la Ville-Es-Cours – Z.I. Sud – 35400 SAINT-MALO – FRANCE

Tel : +33 (0)2 99 58 40 47

E-mail : [contact@roty-tyro.com](mailto:contact@roty-tyro.com)

[www.roty-tyro.com](http://www.roty-tyro.com)






# Swivel abrasive cutting machine – straight or angle cutting

Ref: TPI 8

## STANDARD EQUIPMENT

- Grinder: Ø 355 mm, bore: 25,4 mm
- Motor 7.5 HP, three phase 400 V
- Swivel head & table: 45° left & 45° right
- Oscillating head movement: 80mm (front to back)
- Manual clamping: 1 vice (pneumatic in option)
- Working height: 840 mm
- Length & depth stops
- Welded structure
- Double safety protection: safety cover + electric securities
- Table size: 550 x 340 x 60 mm
- CE certified machine



CUTTING CAPACITIES			
			
90° cut	80	100	160x80
45° cut	70	90	100x50

## OPTIONAL EQUIPMENT

- **LIGHT 24V**
- **PNEUMATIC VICE**
- **SECOND VICE**
- **CUT-OFF WHEELS** : Bore 25.4mm - Disk: Ø 355mm

## ACCESSORIES

- **HORIZONTAL ROLLER CONVEYOR** (*model: metal sheet between rollers*) :
  - Length: 3000 x 200 mm
  - Rollers Ø 40 mm, roller spacing: 333 mm, permissible load: 60 kg/m
- **LENGTH STOP SYSTEM FOR HORIZONTAL ROLLER CONVEYOR** :
  - Includes a graduated slide and a stop slide with locking device and manual removal
  - **GUIDAL WITH GRADUED RULER in mm** : length 1000 mm or more
  - **GUIDAL LCD WITH LCD SCREEN from 0,1 mm** : length 1000 mm or more



# Swivel abrasive cutting machine – straight or angle cutting

Ref: TPI 10



## EQUIPEMENT STANDARD

- Grinder: Ø 355 mm, bore: 25,4 mm
- Motor 10 HP, three phase 400 V
- Swivel head & table: 45° left & 45° right
- Oscillating head movement: 80mm (front to back)
- Manual clamping: 2 vices (pneumatic in option)
- Working height: 840 mm
- Length & depth stops
- Welded structure
- Double safety protection: safety cover + electric securities
- Table size: 550 x 340 x 60mm
- CE certified machine



## CUTTING CAPACITIES

90° cut	90	110	180x90
45° cut	80	100	120x60

## OPTIONAL EQUIPMENT

- **LIGHT 24V**
- **PNEUMATIC VICES (by pair only)**
- **CUT-OFF WHEELS** : Bore 25.4mm – Disk: Ø 355mm

## ACCESSORIES

- **HORIZONTAL ROLLER CONVEYOR** (*model: metal sheet between rollers*) :
  - Length: 3000 x 200 mm
  - Rollers Ø 40 mm, roller spacing: 333 mm, permissible load: 60 kg/m
- **LENGTH STOP SYSTEM FOR HORIZONTAL ROLLER CONVEYOR** :
  - Includes a graduated slide and a stop slide with locking device and manual removal
  - **GUIDAL WITH GRADUED RULER in mm** : length 1000 mm or more
  - **GUIDAL LCD WITH LCD SCREEN from 0,1 mm** : length 1000 mm or more